

MAXIGLIDE SERIES PREMIUM

HIGH PERFORMANCE MINERAL ENGINE OIL



Customer Benefits

Saves on maintenance

Detergent and ashless dispersant additive system provides high temperature deposit control in diesel engines. High oxidation stability protects against the formation of gums and varnish at elevated temperatures, and resists thickening, and oil line and filter plugging.

Longer engine life

Anti-wear additive system protects against wear of critically loaded components under all operating conditions. Multigrade viscosity provides additional protection against wear at start-up and under high temperature operating conditions.

Preserves power and performance

Metallic detergent and ashless dispersant additive system maintains power and performance by providing good upper-ring-belt deposit control, particularly under the high temperatures encountered in turbocharged diesel engines.

Product Specifications

MaxiGlide Series	
SAE Grade	SAE 20W50
Density @ 15 °C, kg/l	0.89
Pour Point, °C	- 24
Flash point, °C	226
Kinematic Viscosity, CST	
@ 40 °C	174.2
@ 100 °C	18.1
Viscosity Index	115.2
Total Base Number, mg KOH/g	8.7

Applications

- Mixed fleets of diesel engines (high speed, four stroke, turbocharged or naturally aspirated)
- Gasoline engines (four stroke) in mixed fleets of both diesel and gasoline engines
- Commercial road transport
- Off-highway vehicles
- Agricultural tractors
- High speed diesel engines in marine service (e.g., fishing boats, river transport)
- Generator sets
- Mobile hydraulic systems (where oil type and viscosity are appropriate)

Performance Standards

Meets the requirements of:

- API SL/CF-4, CF/SG